

View Online at <https://aerobasegroup.com/nsn/5935-00-062-8723>

Thread Class:

2a and 2g

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

3.121 inches

Overall Diameter:

2.470 inches

Environmental Protection:

Humidity resistant and moisture resistant and chemical resistant and pressure proof and corrosion resistant and dust resistant and shock resistant and vibration resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

46.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 8

Thread Size:

1.613 inches and 2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Anodize

Shell Material Specification:

Qq-a-270 federal specification single material response and qq-a-325 federal specification single material response

Insert Material Specification:

Mil-m-14, ty mfh military specification single material response single mating end

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.025 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Acme and acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.