

View Online at <https://aerobasegroup.com/nsn/5935-00-063-1063>

Body Material:

Plastic

Body Style:

Top or bottom mount w/metal saddle

Fabrication Method:

Molded

Overall Length:

Between 1.859 inches and 1.891 inches

Temperature Rating:

100.0 degrees celsius

Overall Height:

1.000 inches

Overall Width:

1.281 inches

Mounting Hole Diameter:

Between 0.140 inches and 0.172 inches

Body Mounting Hole Accommodation Diameter:

Between 1.093 inches and 1.125 inches

Distance Between Mounting Facility Centers:

Between 1.495 inches and 1.505 inches

Mounting Hole Style:

Round, w/two mounting holes

Contact Resistance In Ohms:

0.015

Specific Equipment Accommodated:

Vibrator

Contact Maximum Current Rating In Amps:

5.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold and copper

Accommodated Contact Quantity:

7

Polarization Type:

Contact size

Projection Length Below Mounting Surface:

0.843 inches

Mounting Method:

Saddle

Mounting Type For Which Designed:

Chassis

Contact Position Arrangement Style:

Small

Contact Maximum Voltage In Volts And Current Type:

1250.0 ac and 1250.0 dc

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 tab, solder lug

Specification Data:

81349-mil-s-12883/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300