

View Online at <https://aerobasegroup.com/nsn/5935-00-063-5866>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.531 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Environmental Protection:

Fuel resistant

Unthreaded Mounting Hole Diameter:

Between 0.171 inches and 0.177 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.933 inches and 1.943 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.933 inches and 1.943 inches

Distance From Mounting Shoulder To Front Face:

Between 0.875 inches and 0.885 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

36-10 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

16

Thread Size:

2.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Included Contact Quantity:

48 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Alternate insert position 125.0 deg

Precious Material And Location:

Contact surfaces gold and cOntact surfaces silver

Precious Material And Weight:

0.048 gold grains, troy and 0.048 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0