NSN 5935-00-063-5872

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-063-5872 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Height:** 2.750 inches **Overall Width:** 2.750 inches **Environmental Protection:** Fuel resistant **Unthreaded Mounting Hole Diameter:** Between 0.171 inches and 0.177 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 2.183 inches and 2.193 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.183 inches and 2.193 inches **Distance From Mounting Shoulder To Front Face:** Between 0.875 inches and 0.885 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 40-56 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:**

Externally threaded shell

Thread Length:

0.625 inches

NSN 5935-00-063-5872

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
16
Thread Size:
2.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
85 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Alternate insert position of n
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.085 gold grains, troy and 0.085 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0