NSN 5935-00-064-2596

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-064-2596

Body Style:

Straight shape w/flange

Overall Length:

Between 1.325 inches and 1.336 inches

Overall Height:

Between 1.422 inches and 1.454 inches

Overall Width:

Between 1.422 inches and 1.454 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

Distance From Mounting Shoulder To Front Face:

Between 0.688 inches and 0.698 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

20-41 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

7.5 all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

NSN 5935-00-064-2596 Connector Adapter - Page 2 of 2



Insert Material:
Rubber all mating ends
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
41 2nd mating end all contact groupings
Included Contact Type:
Round socket 2nd mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.082 gold grains, troy and 0.082 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0