

View Online at <https://aerobasegroup.com/nsn/5935-00-064-3048>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Wall type w/ or w/o cover

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-50, 6-50" single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

125.0 single mating end all contact groupings

Shell Type:

Solid

Thread Size:

0.138 inches

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Cadmium single mating end all contact groupings and zinc single mating end all contact groupings

Insert Material:

Plastic single mating end

Shell Material:

Copper alloy

Shell Surface Treatment:

Cadmium and zinc

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

U-socket single mating end 1st contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0