

View Online at <https://aerobasegroup.com/nsn/5935-00-064-3048>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Wall type w/ or w/o cover

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

"3, 5-50, 6-50" single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Shell Type:**

Solid

**Thread Size:**

0.138 inches

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Cadmium single mating end all contact groupings and zinc single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Cadmium and zinc

**Included Contact Quantity:**

2 single mating end 2nd contact grouping

**Included Contact Type:**

U-socket single mating end 1st contact grouping

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0