

View Online at <https://aerobasegroup.com/nsn/5935-00-064-5052>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

Between 0.918 inches and 0.928 inches

Overall Height:

0.718 inches

Overall Width:

Between 0.360 inches and 0.390 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

3

Contact Removability:

Removable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

1.5 all mating ends single contact grouping

Contact Maximum Frequency Rating:

35.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

75.0 all mating ends single contact grouping

Thread Length:

0.125 inches

Thread Size:

0.312 inches and 0.312 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket 3rd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Test Data Document:

10001-2296922 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.