## NSN 5935-00-064-7104

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-064-7104 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 4.906 inches **Overall Height:** Between 2.250 inches and 2.281 inches **Overall Width:** Between 2.250 inches and 2.810 inches **Unthreaded Mounting Hole Diameter:** Between 0.168 inches and 0.183 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.745 inches and 1.755 inches **Distance From Mounting Shoulder To Front Face:** 1.621 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 32-2010-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

NSN 5935-00-064-7104 Electrical Receptacle Connector - Page 2 of 2



Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromium
Included Contact Quantity:
54 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.054 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0