Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-065-0761

## Thread Class:

2a

**Thread Direction:** 

Right-hand

### **Body Style:**

Straight shape, latching

### **Overall Length:**

0.530 inches

#### **Bushing Diameter:**

0.500 inches

### **Overall Width:**

0.780 inches

#### **Diameter:**

0.660 inches

### **Environmental Protection:**

Moisture resistant and corrosion resistant and shock resistant and thermal shock resistant and heat resistant and cold resistant

# Threaded Device Type:

Mounting bushing

#### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

7 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### **Polarization Method:**

Contact

### **Connector Locking Method:**

Friction

#### Thread Length:

0.250 inches

### Thready Qty Per Inch (tpi):

20

# Thread Size:

0.500 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping



Insert Material	
Plastic melamir	ne single mating end
Contact Surfa	ce Treatment Specification:
Mil-g-45204, ty	pe 2, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type	x:
Solder well sing	gle mating end single contact grouping
Contact Mater	ial Specification:
Qq-b-750, com	p a federal specification single material response single mating end single contact grouping
Insert Material	Specification:
Mil-m-14 militar	ry specification single material response single mating end
Included Cont	act Quantity:
7 single mating	end single contact grouping
Bushing Acco	mmodation Hole Shape:
Round	
Included Cont	act Type:
Round socket s	single mating end single contact grouping
Special Featur	res:
Item is shield m	nounted
Precious Mate	rial And Location:
Contact surface	es gold
Precious Mate	rial And Weight:
0.007 gold grai	ns, troy
Precious Mate	rial:
Gold	
Thread Series	Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (militar	ry Standard):
Mil-g-45204 sp	ec.