

View Online at <https://aerobasegroup.com/nsn/5935-00-065-4304>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.562 inches

Overall Diameter:

0.900 inches

Environmental Protection:

Moisture resistant and vibration resistant and corrosion resistant and shock proof

Distance From Mounting Shoulder To Front Face:

Between 0.858 inches and 0.868 inches

Mounting Facility Thickness:

0.284 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

N all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thread Size:

0.625 inches

Contact Surface Treatment:

Gold all mating ends single contact grouping

Shell Material:

Stainless steel

Included Contact Quantity:

2 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.004 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0