NSN 5935-00-067-7486

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-067-7486

Body Style:
Straight shape
Overall Length:
1.556 inches
Overall Height:
Between 0.419 inches and 0.439 inches
Overall Width:
0.509 inches
Environmental Protection:
Salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"2, 15" single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping
Shell Material:

Steel

NSN 5935-00-067-7486

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Shell Material Specification:** Qq-s-398 temp 4 federal specification single material response **Insert Material Specification:** Mil-m-14, type sdg military specification single material response single mating end **Included Contact Quantity:** 15 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.