## NSN 5935-00-068-6000

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-068-6000

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
5.000 inches
Overall Diameter:
1.859 inches
Environmental Protection:
Explosion proof
Cable Entrance Diameter:
Between 0.250 inches and 0.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
B4s single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
20.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
240.0 single mating end single contact grouping
Polarization Method:
Polarization Method: Contact
Contact
Contact Shell Type:
Contact Shell Type: Solid
Contact Shell Type: Solid Connector Locking Method:
Contact Shell Type: Solid Connector Locking Method: Bayonet pin
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method:
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material:
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material: Plastic single mating end
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type:
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type: Solder well single mating end single contact grouping
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material:
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy
Contact Shell Type: Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type: Solder well single mating end single contact grouping Shell Material: Aluminum alloy Included Contact Quantity:

N/a

Shelf Life:

## NSN 5935-00-068-6000

Electrical Plug Connector - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A039b0