Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-069-3764

Body Style:
Straight shape, external coupling
Overall Length:
0.947 inches
Overall Height:
0.812 inches
Overall Width:
0.812 inches
Unthreaded Mounting Hole Diameter:
Between 0.118 inches and 0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.594 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.594 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.441 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
8-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Gold single mating end single contact grouping

## NSN 5935-00-069-3764

Electrical Receptacle Connector - Page 2 of 2



Insert Mater	
-	netic single mating end
	face Treatment Specification:
-	military specification single treatment response single mating end single contact grouping
Terminal Ty	
Solder well s Shell Materi	ingle mating end single contact grouping
Aluminum all	e Treatment:
Anodize	e freatment.
	ontact Quantity:
	ng end single contact grouping
Included Co	
	ngle mating end single contact grouping
	aterial And Location:
Contact surfa	
	aterial And Weight:
0.003 gold gi	
Precious Ma	
Gold	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A039b0	
Mil-std (mili	tary Standard):
NII 45004	spec.