NSN 5935-00-069-7086

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-069-7086 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.781 inches **Overall Height:** 0.531 inches **Overall Width:** 0.375 inches **Unthreaded Mounting Hole Diameter:** 0.086 inches **Distance Between Mounting Facility Centers:** 0.468 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1800.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Screw lock pin Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

NSN 5935-00-069-7086

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.