NSN 5935-00-070-1882

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-070-1882 **Thread Class:** 2b and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.531 inches **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:**

Thready Qty Per Inch (tpi): 18 and 32

Internally threaded coupling ring

NSN 5935-00-070-1882

Electrical Receptacle Connector - Page 2 of 2



| Thread Size: |
|--|
| 1.375 inches and 0.190 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium and chromate |
| Included Contact Quantity: |
| 19 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.019 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef and unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |