Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-071-3254

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape threaded
Overall Length:
Between 1.495 inches and 1.505 inches
Overall Diameter:
Between 2.933 inches and 2.943 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Distance From Mounting Shoulder To Front Face:
Between 1.214 inches and 1.224 inches
Mounting Facility Thickness:
Between 0.031 inches and 0.250 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
28-11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.750 inches and 1.750 inches



**Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Included Contact Quantity:** 4 single mating end 1st contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact material silver **Precious Material And Weight:** 0.004 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Uns and uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0