NSN 5935-00-071-7404

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-071-7404

Thread Direction: Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 3.770 inches **Overall Height:** 0.453 inches **Overall Width:** Between 0.521 inches and 0.541 inches **Environmental Protection:** Moisture proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.128 inches **Distance Between Mounting Facility Centers:** Between 3.485 inches and 3.515 inches **Board Accommodated Length:** 2.805 inches single board **Board Accommodated Width:** Between 0.054 inches and 0.070 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Shell Type: Solid **Terminal Location:** Front single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping

Shell Material:

Plastic diallyl phthalate

NSN 5935-00-071-7404

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.029 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21097/4 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No