NSN 5935-00-071-7461

Tip Jack - Page 1 of 2

Gold spring and silver spring



View Online at https://aerobasegroup.com/nsn/5935-00-071-7461

Electrical Insulation Feature: Insulated completely Identification Code Color: Brown Body Style: Press fit Overall Length: 0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Identification Code Color: Brown Body Style: Press fit Overall Length: 0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Brown Body Style: Press fit Overall Length: 0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Body Style: Press fit Overall Length: 0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Press fit Overall Length: 0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Overall Length: 0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.340 inches Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Body Length: 0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.220 inches Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Overall Diameter: 0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.218 inches Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Bushing Accommodation Hole Shape: Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Round Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Accommodated Finger Type: Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Test prod single finger Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Finger Accommodation Diameter: 0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.090 inches single finger Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Finger Accommodation Length: 0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.140 inches single finger Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Bushing Thru-hole Accommodation Diameter: 0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
0.185 inches Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Capacitance In Picofarads: 0.6 Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Mounting Facility Type And Quantity: 1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
1 bushing Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Terminal Type: Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Tab, solder lug Material: Plastic, polytetrafluoroethylene body
Material: Plastic, polytetrafluoroethylene body
Plastic, polytetrafluoroethylene body
Material:
Plastic polytetrafluoroethylene insulator
Precious Material And Location:
Spring contact and terminal surfaces gold and spring contact and terminal surfaces silver
Precious Material:
Gold and silver
Surface Treatment:
Gold and silver terminal

NSN 5935-00-071-7461

Tip Jack - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400