Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-071-9927

Thread Class: 2a **Thread Direction: Right-hand Body Style:** Straight shape, external coupling **Overall Length:** 1.141 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Environmental Protection:** Watertight **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.901 inches and 0.911 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.901 inches and 0.911 inches **Distance From Mounting Shoulder To Front Face:** Between 0.532 inches and 0.562 inches **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.450 inches Thready Qty Per Inch (tpi): 20

NSN 5935-00-071-9927

Electrical Receptacle Connector - Page 2 of 2



Thread Size: 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.004 gold grains, troy and 0.004 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0
