Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-072-1125

Thread Cla	əə.
2a	
Body Style	
•	pe, external coupling
Overall Ler	ngth:
1.625 inche	S
Overall Hei	ght:
Between 1.3	344 inches and 1.406 inches
Overall Wid	ith:
Between 1.3	344 inches and 1.406 inches
Distance B	etween Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inche	S
Distance F	rom Mounting Shoulder To Front Face:
0.750 inche	S
Threaded [	Device Type:
Coupling fa	sility
Mating End	Quantity:
1	
Contact Po	sition Arrangement Style:
18-4 single	mating end
Contact Re	movability:
Nonremova	ble single mating end single contact grouping
Contact Ma	ximum Current Rating In Amps:
22.0 single	mating end single contact grouping
Contact Ma	ximum Ac Voltage Rating In Volts:
900.0 single	e mating end single contact grouping
Contact Ma	ximum Dc Voltage Rating In Volts:
1250.0 sing	le mating end single contact grouping
Polarizatio	n Method:
Keyway or r	nultiple keyway
	tion In Deg:
0.0	
Shell Type:	
Solid	
Connector	Locking Method:
	nreaded shell
Thread Ler	
0.625 inche	-
Thread Size	
1.125 inche	
	ce Treatment:
Cadmium	

# NSN 5935-00-072-1125

Electrical Receptacle Connector - Page 2 of 2



## Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## Included Contact Quantity:

4 single mating end single contact grouping

# Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

---

### Demilitarization:

No

#### Fiig:

A039b0