NSN 5935-00-072-3082

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-072-3082

Thread Class:
2a
Thread Direction:
Right-hand
Overall Height:
1.200 inches
Overall Width:
1.200 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Coupling facility
Contact Position Arrangement Style:
14s-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
20
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Ob all Marketicals
Shell Material:
Aluminum alloy
Aluminum alloy
Aluminum alloy Shell Surface Treatment:
Aluminum alloy Shell Surface Treatment: Nickel
Aluminum alloy Shell Surface Treatment: Nickel Included Contact Quantity:
Aluminum alloy Shell Surface Treatment: Nickel Included Contact Quantity: 5 single mating end single contact grouping
Aluminum alloy Shell Surface Treatment: Nickel Included Contact Quantity: 5 single mating end single contact grouping Included Contact Type:

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

NSN 5935-00-072-3082

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0