NSN 5935-00-072-3083

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-072-3083 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Height:** 1.200 inches **Overall Width:** 1.200 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Coupling facility **Contact Position Arrangement Style:** 14s-5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

NSN 5935-00-072-3083

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A039b0