NSN 5935-00-072-3087

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-072-3087

Body Style: Right angle type **Overall Length:** 2.115 inches **Overall Height:** 0.460 inches Overall Width: 0.408 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** 1.825 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end **Connector Cable Strain Relief Method: Bracket Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Wire wrap single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a, ht federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14f, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 9 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-00-072-3087

Electrical Receptacle Connector - Page 2 of 2



S	pe	cia	l F	ea	tui	es
---	----	-----	-----	----	-----	----

Contact numbers 1, 2, 3, 5, 7, 9, 10, 11, 13, 14, 15, 17, 18, 19, 21, 22, 23, 25, 26, 27, 29 and 30 missing

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.