## NSN 5935-00-073-1873

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-073-1873 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 1.330 inches and 1.350 inches **Overall Height:** Between 0.515 inches and 0.547 inches **Overall Width:** 0.270 inches **Environmental Protection:** Vibration resistant and shock resistant and pressure proof and humidity resistant **Distance Between Mounting Facility Centers:** 1.094 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 29 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 2.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping

Insert Material:

Plastic single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-073-1873

Electrical Receptacle Connector - Page 2 of 2



| U | lna | ble | To | Deco | de: |
|---|-----|-----|----|------|-----|
|   |     |     |    |      |     |

Unable to decode and unable to decode

**Included Contact Quantity:** 

29 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0