## NSN 5935-00-073-4149

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-073-4149

Body Style:
Angle, shape, internal coupling
Overall Length:
1.125 inches
Overall Height:
0.812 inches
Overall Diameter:
0.500 inches
Environmental Protection:
Watertight
Cable Entrance Diameter:
0.242 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Dm single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
180.0
Shell Type:
Shell Type: Solid
Solid
Solid  Connector Locking Method:
Solid  Connector Locking Method:  Bayonet shell
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:  50.0 single mating end single contact grouping
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:  50.0 single mating end single contact grouping  Terminal Location:
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:  50.0 single mating end single contact grouping  Terminal Location:  Back single mating end single contact grouping
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:  50.0 single mating end single contact grouping  Terminal Location:  Back single mating end single contact grouping  Insert Material:
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:  50.0 single mating end single contact grouping  Terminal Location:  Back single mating end single contact grouping  Insert Material:  Plastic tetrafluoroethylene single mating end
Solid  Connector Locking Method:  Bayonet shell  Connector Cable Strain Relief Method:  Cable clamp  Radio Frequency Type Contact Characteristic Impedance In Ohms:  50.0 single mating end single contact grouping  Terminal Location:  Back single mating end single contact grouping  Insert Material:  Plastic tetrafluoroethylene single mating end  Terminal Type:
Connector Locking Method: Bayonet shell Connector Cable Strain Relief Method: Cable clamp Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type: Crimp single mating end single contact grouping
Connector Locking Method: Bayonet shell Connector Cable Strain Relief Method: Cable clamp Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material:
Connector Locking Method: Bayonet shell Connector Cable Strain Relief Method: Cable clamp Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type: Crimp single mating end single contact grouping Shell Material: Copper alloy

1 single mating end single contact grouping

## NSN 5935-00-073-4149

Electrical Plug Connector - Page 2 of 2



Coaxial pin single mating end single contact grouping

**Precious Material And Location:** 

Shell surface gold

**Precious Material And Weight:** 

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0