Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-074-3083



Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.562 inches

Overall Diameter:

1.250 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Potting type

Thread Length:

0.536 inches

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

20

Thread Size:

1.000 inches

NSN 5935-00-074-3083 Electrical Plug Connector - Page 2 of 2



	al Location:		
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping			
		Insert N	
			single mating end
	Surface Treatment Specification:		
	5 federal specification single treatment response single mating end single contact groupin		
Termina			
	vell single mating end single contact grouping		
Shell Ma			
Aluminu	m alloy		
Shell Su	urface Treatment:		
Cadmiu	m and chromate		
Include	d Contact Quantity:		
2 single	mating end single contact grouping		
Include	d Contact Type:		
Round s	ocket single mating end single contact grouping		
Preciou	s Material And Location:		
Contact	surfaces silver		
Preciou	s Material And Weight:		
0.010 si	ver grains, troy		
Preciou	s Material:		
Silver			
Thread	Series Designator:		
Unef			
Shelf Li	fe:		
N/a			
Unit Of	Measure:		
Demilita	arization:		
No			
Fiig:			