Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-074-3980

Right-hand Overall Length: 1.375 inches Overall Height: 1.094 inches Overall Width: 1.094 inches Overall Width: 1.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Curvent Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Chread Size: 0.750 inches Insert Material: Alurninum alloy	Thread Direction:
Overall Length: 1.375 inches Overall Height: 1.094 inches Overall Width: 1.094 inches Overall Vidth: 1.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Coupling nut Thready Guy Per Inch (tpi): 20 Sinches Insert Material: Rubber synthetic single mating end single contact grouping Cheed Contact Quantity:	
1.375 inches Overall Height: 1.094 inches Overall Width: 1.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quarts 2 20.0 single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Connect Locking Method: Internally threaded coupling nut Thread Size 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Firead Size National Size Insert Material: Ruber synthetic single mating end </td <td>с С</td>	с С
Overall Height: 1.094 inches Overall Width: 1.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Height: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Current Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Cv Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Interaded coupling nut Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Material: Auminum alloy Included Contact Quantity: 2 single mating end single contact grouping Foreid Features: Auzer Partice Single mating end single contact grouping Foreid Size <tr< td=""><td>-</td></tr<>	-
1.094 inches Coverall Width: 1.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Current Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Interaded coupling nut Threaded Size: 0.750 inches Insert Material: Ruber synthetic single mating end Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Field Material: Ruber synthetic single mating end Internal Single Fined Material:	
Overall Width:1.094 inchesCenter To Center Distance Between Mounting Facilities Parallel To Height:0.812 inchesDistance Between Centerlines Of Mounting Facilities Parallel To Body Widthh:0.812 inchesCable Entrance Diameter:0.484 inchesThreaded Device Type:Coupling facilityMating End Quantity:122.0 single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Current Rating In Volts:500.0 single mating end single contact groupingContact Maximum Curlent Rating In Volts:700.0 single mating end single contact groupingContact Maximum Curlent Rating In Volts:700.0 single mating end single contact groupingContact Maximum Curlent GroupingConnector Locking Method:Internally threaded coupling nutThready Qty Per Inch (tpi):20Thread Size:0.750 inchesInsert Material:Auuminum alloyIncluded Contact Quantity:2 single mating end single contact groupingCherder Contact Quantity:2 single mating end single contact groupingIncluded Contact Type:Round pin single mating end single contact grouping <td< td=""><td>-</td></td<>	-
1.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Current Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Cu Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single contact grouping Included Contact Quantity: 2 single mating	
Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Coupling facility Mating End Quantity: 1 Coupling mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Childed Contact Quantity: 2 single mating end single contact grouping Pacilities Pacili	
0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Interaded coupling nut Threaded Size: 0.750 inches Insert Material: Rubber synthetic single mating end Murinum alloy Included Contact Quantity: 2 single mating end single contact grouping Forluded Contact Quantity: 2 single mating end single contact grouping Butterial: Rubber synthetic single mating end Butterial: Rubber synthetic single contact grouping Included Contact Quantity: 2 single mating end single contact grouping <td< td=""><td></td></td<>	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Hasterial: Rubber synthetic single mating end Material: Aluminum alloy Included Contact Type: 2 single mating end single contact grouping Christer Material: Rubrer all Rubrer all Rubrer all Policited Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end sin	
0.812 inches Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Bige rating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	
Cable Entrance Diameter: 0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping <td></td>	
0.484 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Contact Quantity: 2 single mating e	
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Size:	Cable Entrance Diameter:
Coupling facility Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Contact Quantity: Polarized; 4 mtg holes Thread Series Designator:	0.484 inches
Mating End Quantity: 1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Ruber synthetic single mating end Shell Material: Aluminum alloy Included Contact Type: Round pin single end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Threaded Device Type:
1 Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Forcial Features: Polarized; 4 mtg holes Thread Size:	Coupling facility
Contact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 single mating end single contact groupingConnector Locking Method:Internally threaded coupling nutThready Qty Per Inch (tpi):20Thread Size:0.750 inchesInsert Material:Rubber synthetic single mating endShell Material:Aluminum alloyIncluded Contact Quantity:2 single mating end single contact groupingForlade Size:9 single mating end single contact groupingPolarized; 4 mtg holesFueral Size:Polarized; 4 mtg holes	Mating End Quantity:
 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator: 	1
Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	Contact Maximum Current Rating In Amps:
500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	22.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	Contact Maximum Ac Voltage Rating In Volts:
700.0 single mating end single contact grouping Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	500.0 single mating end single contact grouping
Connector Locking Method: Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	Contact Maximum Dc Voltage Rating In Volts:
Internally threaded coupling nut Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	700.0 single mating end single contact grouping
Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	Connector Locking Method:
20 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes	Internally threaded coupling nut
 Thread Size: 0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator: 	Thready Qty Per Inch (tpi):
0.750 inches Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	20
Insert Material: Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Thread Size:
Rubber synthetic single mating end Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	0.750 inches
Shell Material: Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Insert Material:
Aluminum alloy Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Rubber synthetic single mating end
Included Contact Quantity: 2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Shell Material:
2 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Aluminum alloy
Included Contact Type: Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	Included Contact Quantity:
Round pin single mating end single contact grouping Special Features: Polarized; 4 mtg holes Thread Series Designator:	2 single mating end single contact grouping
Special Features: Polarized; 4 mtg holes Thread Series Designator:	Included Contact Type:
Polarized; 4 mtg holes Thread Series Designator:	Round pin single mating end single contact grouping
Thread Series Designator:	Special Features:
-	Polarized; 4 mtg holes
Unef	Thread Series Designator:
	Unef

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0