

View Online at <https://aerobasegroup.com/nsn/5935-00-074-4444>

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

1.797 inches

**Body Angle In Deg:**

90.0

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

**Cable Entrance Diameter:**

Between 0.631 inches and 0.666 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

24-61 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

270.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

3.037 inches

**Distance From Centerline To Cable End:**

Between 1.219 inches and 1.281 inches

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 257.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Insert Material Specification:**

Mil-r-3065 military specification single material response single mating end

**Included Contact Quantity:**

61 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.061 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.