

View Online at <https://aerobasegroup.com/nsn/5935-00-076-8597>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.175 inches

Overall Diameter:

Between 0.740 inches and 0.760 inches

Environmental Protection:

Heat resistant

Cable Entrance Diameter:

0.096 inches

Distance From Mounting Shoulder To Front Face:

Between 0.780 inches and 0.800 inches

Mounting Facility Thickness:

0.469 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.476 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Qq-n-290, cl 2 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290, class 2 federal specification single treatment response

Shell Material Specification:

Qq-b-626, comp 22, 1/2 h federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0