Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-078-1530

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
0.828 inches
Overall Diameter:
1.266 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
Between 0.691 inches and 0.722 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.125 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
12-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Tin single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-t-10727, type 1 military specification single treatment response single mating end single contact grouping



Terminal Type:

Solder well single mating end single contact grouping

Included Contact Quantity:

3 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Test Data Document:

81349-mil-dtl-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

81349-mil-dtl-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-t-10727 spec.