

View Online at <https://aerobasegroup.com/nsn/5935-00-078-6019>

Body Style:

Straight edge type w/mounting flange

Overall Length:

5.500 inches

Overall Height:

1.625 inches

Overall Width:

Between 0.485 inches and 0.505 inches

Environmental Protection:

Salt water resistant

Unthreaded Mounting Hole Diameter:

0.130 inches

Distance Between Mounting Facility Centers:

Between 5.190 inches and 5.210 inches

Board Accommodated Length:

4.610 inches single board and 4.620 inches single board

Board Accommodated Width:

0.093 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-330, comp a federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd military specification single material response single mating end

Included Contact Quantity:

46 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.046 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.