

View Online at <https://aerobasegroup.com/nsn/5935-00-078-9336>

Body Style:

Straight shape, external coupling

Overall Length:

0.835 inches

Overall Height:

1.562 inches

Overall Width:

1.562 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Cable Entrance Diameter:

1.187 inches

Distance From Mounting Shoulder To Front Face:

0.562 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

22-48 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

45.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Crimp type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

48 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0