NSN 5935-00-079-3982

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-079-3982

view Offline at https://aerobasegroup.com/hist//3355-00-073-3362
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
1.250 inches
Overall Diameter:
1.513 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
37p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
50.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping

Contact surface gold

Precious Material And Location:

NSN 5935-00-079-3982

Electrical Plug Connector - Page 2 of 2



Gold

Test Data Document:

81349-mil-c-81703 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0