

View Online at <https://aerobasegroup.com/nsn/5935-00-079-4397>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.797 inches and 0.891 inches

Overall Height:

Between 2.297 inches and 2.328 inches

Overall Width:

Between 2.297 inches and 2.328 inches

Unthreaded Mounting Hole Diameter:

Between 0.164 inches and 0.174 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.939 inches and 1.949 inches

Distance From Mounting Shoulder To Front Face:

Between 0.484 inches and 0.516 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Ic-v20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

30.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

6

Thread Size:

2.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface silver

Precious Material And Weight:

0.420 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0