NSN 5935-00-079-5462

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-079-5462 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Overall Length:** 1.438 inches **Overall Height:** 0.375 inches **Overall Width:** 0.609 inches **Mounting Hole Diameter:** 0.140 inches **Body Mounting Hole Accommodation Length:** 1.000 inches **Body Mounting Hole Accommodation Width:** 1.000 inches **Mounting Hole Style:** Rectangular, w/four mounting holes/slots **Contact Maximum Current Rating In Amps:** 3.0 **Contact Material:** Phosphor bronze **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity:** 14 Center To Center Distance Between Outside Mounting Holes Along Length: 0.400 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 0.641 inches Polarization Type: Colored dot **Projection Length Below Mounting Surface:** 0.222 inches **Mounting Method:**

Threaded stud

Mounting Type For Which Designed:
Chassis

NSN 5935-00-079-5462 Plug-in Electronic Components Socket - Page 2 of 2



| Thready Qty Per Inch (tpi): |
|---|
| 32 |
| Thread Size: |
| 0.138 inches |
| Contact Position Arrangement Style: |
| Symmetrical |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.014 gold grains, troy and 0.014 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 14 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . - |
| Demilitarization: |
| No |
| Fiig: |
| Δ02300 |