NSN 5935-00-079-5910

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-079-5910

view Online at https://aerobasegroup.com/nsn/5935-00-079-5910
Body Style:
Straight shape
Overall Length:
Between 5.078 inches and 6.108 inches
Overall Height:
0.840 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.149 inches
Distance Between Mounting Facility Centers:
Between 4.474 inches and 4.494 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1800.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Turret single mating end single contact grouping
Shell Material:
Aluminum alloy
Insert Material Specification:
Mil-m-14, type mme military specification single material response single mating end
Included Contact Quantity:

moradou comact quantity

23 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-00-079-5910

Electrical Receptacle Connector - Page 2 of 2



Precious	Material	And	Location:
----------	----------	-----	-----------

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.023 gold grains, troy and 0.023 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.