## NSN 5935-00-079-5911

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-079-5911

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.307 inches and 2.317 inches

**Overall Height:** 

Between 0.911 inches and 0.931 inches

**Overall Width:** 

Between 0.870 inches and 0.880 inches

**Distance Between Mounting Facility Centers:** 

Between 1.997 inches and 2.003 inches

**Threaded Device Type:** 

Mounting stud

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

42 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

7.5 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

500.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

**Connector Locking Method:** 

Jackscrew-socket

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:** 

Plastic polyester single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Included Contact Quantity:** 

42 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

## NSN 5935-00-079-5911

Electrical Receptacle Connector - Page 2 of 2



0.042 gold grains, troy and 0.042 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0