# NSN 5935-00-079-8446

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-079-8446

## **Body Style:**

Straight shape, external coupling w/backshell

## **Overall Length:**

1.187 inches

## **Overall Height:**

1.302 inches

#### **Overall Width:**

1.302 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.964 inches and 0.974 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.964 inches and 0.974 inches

## **Distance From Mounting Shoulder To Front Face:**

0.542 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

2724 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Polarization Method:**

Key, multiple key groove

## **Insert Position In Deg:**

0.0

## Shell Type:

Solid

# **Connector Locking Method:**

Detent

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

# Terminal Type:

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# NSN 5935-00-079-8446

Electrical Receptacle Connector - Page 2 of 2



## Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Included Contact Quantity:**

24 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surface gold

## **Precious Material:**

Gold

## Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Shelf Life:** 

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A039b0