NSN 5935-00-080-2943

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-080-2943 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, latching **Overall Length:** 0.781 inches **Bushing Diameter:** 0.515 inches **Overall Width:** 0.719 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Latching ring Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.800 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Included Contact Quantity:** 5 single mating end single contact grouping **Bushing Accommodation Hole Shape:**

Round

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-00-080-2943

Electrical Receptacle Connector - Page 2 of 2



Precious	Material And	Location:
riecious	IVIALEITAI ATTU	LUCALIUII.

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0