## NSN 5935-00-080-2944

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-080-2944 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.812 inches **Overall Height:** 0.438 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Frequency Rating:** 500.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 48.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** 

Copper alloy

NSN 5935-00-080-2944 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Silver	
ncluded Contact Quantity:	
1 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round	
ncluded Contact Type:	
Coaxial pin single mating end single contact grouping	
Precious Material And Location:	
Contact and shell surfaces silver	
Precious Material And Weight:	
0.105 silver grains, troy	
Precious Material:	
Silver	
Thread Series Designator:	
Jnef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
4039b0	