

View Online at <https://aerobasegroup.com/nsn/5935-00-080-4936>

Overall Height:

Between 0.419 inches and 0.439 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Body Length:

Between 2.972 inches and 3.003 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

1.625 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

25 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

425.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel comp 1017

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Shell Material Specification:

Qq-s-636 federal specification single material response

Insert Material Specification:

Mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.025 gold grains, troy and 0.025 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-8384 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-8384 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.