## NSN 5935-00-080-5458

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-080-5458

**Body Style:** 

Angle shape w/cable clamp

**Overall Diameter:** 

1.672 inches

**Body Angle In Deg:** 

90.0

**Environmental Protection:** 

Corrosion resistant and moisture resistant

**Cable Entrance Diameter:** 

Between 0.490 inches and 0.525 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

22-55 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet slot

**Connector Cable Strain Relief Method:** 

Cable clamp

**Distance From Centerline To Connector End:** 

1.511 inches

**Distance From Centerline To Cable End:** 

Between 1.108 inches and 1.170 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

Insert Material:

Rubber chloroprene class cr single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

## **NSN 5935-00-080-5458**Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0