Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-080-6625

**Body Style:** Right angle type **Overall Length:** 4.594 inches **Overall Height:** 0.469 inches **Overall Width:** 0.750 inches **Body Length:** 4.594 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers:** 4.250 inches **Board Accommodated Width:** 0.062 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 875.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** 

Aluminum alloy

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
23 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.023 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec

Mil-m-14 spec.