

View Online at <https://aerobasegroup.com/nsn/5935-00-080-9051>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling strain relief

Overall Height:

1.000 inches

Overall Width:

1.000 inches

Body Length:

1.971 inches

Environmental Protection:

Corrosion resistant

Unthreaded Mounting Hole Diameter:

0.112 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

Distance From Mounting Shoulder To Front Face:

0.890 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

C single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact and shell surface silver

Precious Material And Weight:

0.001 gold grains, troy and 0.001 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0