Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-081-0417

# Body Style:

Straight shape, external coupling strain relief

# **Overall Height:**

1.781 inches

# **Overall Width:**

1.781 inches

#### Body Length:

2.250 inches

#### **Environmental Protection:**

Pressure proof

### **Unthreaded Mounting Hole Diameter:**

### 0.120 inches

### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.437 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

### Cable Entrance Diameter:

0.750 inches

# Distance From Mounting Shoulder To Front Face:

0.531 inches

# Mating End Quantity:

1

### **Contact Position Arrangement Style:**

61 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

2000.0 single mating end single contact grouping

### Contact Maximum Dc Voltage Rating In Volts:

2500.0 single mating end single contact grouping

### **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

75.0

#### Shell Type:

Solid

### **Connector Locking Method:**

Snap ring

### **Connector Cable Strain Relief Method:**

Cable clamp

# NSN 5935-00-081-0417

Electrical Receptacle Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Ceramic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 61 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0