## NSN 5935-00-081-4170

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-081-4170 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/cable clamp **Overall Diameter:** 1.250 inches **Body Angle In Deg:** 90.0 **Environmental Protection:** Moisture resistant and vibration resistant **Cable Entrance Diameter:** 0.562 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **Distance From Centerline To Connector End:** 2.156 inches

2.156 inches

Distance From Centerline To Cable End:

1.531 inches

## NSN 5935-00-081-4170

Electrical Plug Connector - Page 2 of 2



Thread Length:
0.723 inches
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
20
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.010 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0