Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-081-7810

Body Style:

Straight shape

Overall Length:

2.088 inches

Overall Height:

0.631 inches

Overall Width:

0.494 inches

Environmental Protection:

Heat resistant and cold resistant and corrosion resistant and moisture resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.086 inches

Distance Between Mounting Facility Centers:

1.852 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"b, 17w2" single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end all contact groupings

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd

treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end 2nd contact grouping

Shell Material:

Steel

NSN 5935-00-081-7810

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Shell Material Specification:** Qq-s-698 federal specification single material response **Insert Material Specification:** Mil-p-19833, ty gdi-30f military specification single material response single mating end or mil-m-14, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 2 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end 2nd contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.017 gold grains, troy and 0.017 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.