NSN 5935-00-081-8824

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-081-8824 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 2.750 inches **Overall Diameter:** 1.890 inches **Environmental Protection:** Moisture resistant and vibration resistant **Cable Entrance Diameter:** 0.735 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-7 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 245.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1250.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1750.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg: Shell Type:** Solid

0.0

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.724 inches

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

NSN 5935-00-081-8824Electrical Plug Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18
Thread Size:
1.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0