

View Online at <https://aerobasegroup.com/nsn/5935-00-082-0587>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

T-shape

Overall Length:

1.313 inches

Overall Height:

1.141 inches

Overall Width:

0.594 inches

Environmental Protection:

Pressure proof and humidity resistant and moisture proof and salt water resistant and vibration proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

7.5 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1500.0 all mating ends all contact groupings

Contact Maximum Frequency Rating:

5500.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded coupling nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thread Size:

0.438 inches and 0.438 inches

Contact Material:

Copper alloy 3rd mating end all contact groupings

Insert Material:

Plastic all mating ends

Contact Material Specification:

Qq-b-613 federal specification single material response 1st mating end all contact groupings and qq-b-626 federal specification 1st material response 1st mating end all contact groupings

Shell Material:

Copper alloy

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 3rd mating end all contact groupings

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-h-7199 spec.